

S4 AURORA Paramagnetic Oxygen Analyser



Paramagnetic Oxygen Analysers for accurate percent measurements in combustion testing, inert atmospheres, medical and safety for humans, internal combustion engine exhaust and many more applications.

Flexible

- Many different configurations
- Programmable contact closure for gas path control

Easy to Use

- Touch-screen colour display
- Remote software suite for control over the Internet

Accurate

- 0.1% O₂ resolution
- 0.1% linearity



Non-screen Version
available for system
integrators



S4 AURORA

Signal Series 4 AURORA Paramagnetic Oxygen Analyser

Oxygen is possibly the most measured of all gases. Essential for all life on Earth, it is also required for combustion and a wide range of industrial processes.

The Paramagnetic Oxygen analyser will remain in operation for many years giving accurate and dependable readings. Essentially, users can almost fit it and forget it, because it is likely to be the most reliable of gas analysers.



The Signal series 4 platform augments this reliability with embedded firmware and remote operational software running over Ethernet. Each analyser has its own individual I.P. address, which provides the operator with functionality such as:

- remote data logging
- analyser set-up
- gas path configuration
- fault log examination
- remote viewing of important tests or processes

In recent years electrochemical sensors have become widely available and these have improved significantly. Their advantages are their small size and negligible power requirement. They have therefore been widely used for safety applications in confined spaces. However, they have a short life span; typically lasting for up to 2 years before replacement is necessary. Of course this is unacceptable in a fixed industrial process or in testing laboratories where operational uptime and maintenance costs are important.

SPECIFICATIONS

DETECTOR TYPE: Paramagnetic. 'Dumb bell' servo driven.

RANGES:

Range A: 0-5%, 0-10%, 0-25%. or
Range B: 0-100% or
Range C: 95-100%

NOISE: 0.005% O₂.

LINEARITY: +/- 0.1% O₂

REPEATABILITY: < +/- 0.01% O₂

ZERO DRIFT: < +/- 0.2% O₂ per 30 days

RESPONSE TIME: < 2.5s

FLOW EFFECT:

1% change in reading with flow change of 0.5 l/min to 3 l/min into atmospheric pressure.

TEMPERATURE EFFECT:

0.005% O₂ change on Zero reading with temperature change of 5 to 40 °C.
0.015% O₂ change on span reading with temperature change of 5 to 40 °C.

TILT EFFECT: 0.01% O₂ per degree of tilt.

EXTERNAL MAGNETIC EFFECT:

A mass of soft magnetic material anywhere on the enclosure will cause less than 0.1 % O₂ change in reading.

CONSTRUCTION:

Wetted parts, 316 Stainless steel and Quartz

DIMENSIONS:

19" X 133.3mm X 550mm
Weight: 12 Kg

POWER REQUIREMENTS: 110VAC - 250VAC or 24VDC. 70 Watts.

OUTPUTS:

0-10 volts
RS232
Ethernet (remote software is included)
Optional 4-20 mA.

GAS CALIBRATION SERVICES:

Nitrogen (to set analyser zero)
Oxygen in Nitrogen of appropriate concentration for calibration. Or room air.

OPTIONAL:

Atmospheric barometric pressure compensation

Authorised Representative:

Signal Group Ltd

Standards House, Doman Road, Camberley, Surrey GU15 3DF
United Kingdom

Tel: +44 (0)1276 682841 Email: sales@signal-group.com



www.signal-group.com



ISO
9001 : 2015
REGISTERED

Cert No. 317012019

Specifications may be changed without notification