

S4 SOLAR XPLORE

Portable heated FID VOC analyser



Flame Ionisation Detector (FID) analysers for the discontinuous measurement of the mass concentration of gaseous and vaporous organic substances in stationary source emissions.

Flexible

- Single or dual detectors
- Integrated zero air generator
- Software suite for use over ethernet

Easy to Use

- Rugged and portable
- Wireless tablet interface
- Typical warm up 30 minutes

Accurate

- Precision monobloc heated FID
- Simultaneous monitoring of THC, NMHC & Methane
- Fast response time



Rack mounted FID for continuous monitoring

S4 SOLAR XPLORE

SPECIFICATIONS

MEASUREMENT TECHNIQUE

Flame Ionisation Detector

MEASURING UNITS

PPM or mg user selectable

MEASURING RANGES

Range A: 0-1000ppm.

User settable to e.g. 0-1ppm, 0-5ppm, 0-10ppm, 0-50ppm, 0-100ppm, 0-500ppm, 0-1000ppm.
Resolution: 0.01 ppm

Range B: 0-10000ppm.

User settable to e.g. 0-10ppm, 0-50ppm, 0-100ppm, 0-500ppm, 0-1000ppm, 0-5000ppm. 0-10,000ppm.
Resolution: 0.1ppm

Range C: 0-100,000 ppm.

User settable, with resolution of 1ppm

RESPONSE TIME

THC <1.5 secs
CH4 and NMHC <2.5 secs

REPEATABILITY

<1% FSD

OXYGEN EFFECT

<2% of reading from
0% to 21% WITH C₃H₈

LINEARITY

± 0.5% FSD OR 2% of reading

DRIFT

< ± 0.2ppm or ± 2% range
whichever greater

NOISE

<0.05% FSD, THC & CH₄
(EURO VII)

TEMPERATURE EFFECT ON ZERO

<0.15% per °C

TEMPERATURE EFFECT ON SPAN

<0.3% per °C

SAMPLE INLET PRESSURE

With internal sample pump:

-0.6 to +0.4bar

Without internal sample pump:

+0.2 to +0.5bar

ACCURACY

<0.2% FSD

PRECISION

<1%

DETECTION LIMIT

0.05mgC/m³

BYPASS FLOW SENSITIVITY

Less than 2% from
1 to 3 L/min

SAMPLE FILTER

Removable 0.4 micron PTFE
7um non removable stainless
steel filter for CFID

DISPLAY

Blank or Detachable Screen

SAMPLE CONDITION

0-200°C (Heated version)

0-80°C non-condensing for
CFID

FUEL CONSUMPTION

Single detector:

35ml/min H₂ or 180ml/min
H₂He

Dual detectors:

70ml/min H₂ or 360ml/min
H₂He

AIR SUPPLY

Single detector:

<1.1L/min

Dual detector:

<1.6L/min

OPERATING CONDITIONS

5-40°C ambient temperature

OUTPUTS

0-10 Vdc

RS232

Ethernet

TCP/IP

Optional 4-20 mA

POWER REQUIREMENTS

100 to 250Vac

Optional 24VDC

600W max

REMOTE CONTROL

AK protocol

Ethernet

Comes with S4i remote
software operating system.

SIZE AND WEIGHT

252 (w) x 264 (h) x 494 (d) mm

14kg - 16kg

IP RATING

IP55

NEW - Every S4 gas analyser can now be supplied with a rugged, wireless tablet which connects wirelessly to the analyser via an inbuilt 802.11 Wi-Fi that can connect up to 50 metres away. This provides the users with the ability to view live data in a different location, and even manage data logging, alarms and calibrations.



Authorised Representative:



www.signal-group.com

Signal Group Ltd

Standards House, Doman Road, Camberley, Surrey GU15 3DF
United Kingdom

Tel: +44 (0)1276 682841 Email: sales@signal-group.com



ISO
9001 : 2015
REGISTERED

Cert No. 317012019